

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 02/02/2021 Reviewed on 02/02/2021

1 Identification

- · Product Identifier
- · Trade Name: Artificial Sebum. ASTM D4265 14
- · Product Number: 1700-0700. 1700-0702
- · Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available.

- · Product Description: Artificial Sebum according to ASTM D4265 14
- · Details of the Supplier of the Safety Data Sheet:
- Manufacturer/Supplier:
 Pickering Laboratories, Inc.
 1280 Space Park Way
 Mountain View, CA 94043
 Phone: (650) 694-6700

Fax: (650) 968-0749 www.pickeringlabs.com support@pickeringlabs.com

Emergency telephone number:

Clean Harbors Environmental Services

1-800-645-8265

2 Hazard(s) Identification

· Classification of the substance or mixture:



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- · Label elements:
- · Hazard pictograms:



- · Signal word: Warning
- · Hazard statements:

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· Precautionary statements:

P264 Wash thoroughly after handling.

P280 Wear protective gloves / eye protection / face protection.

P302+P352 If on skin: Wash with plenty of water.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet). P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P337+P313 If eye irritation persists: Get medical advice/attention.

Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values. 30 % of the mixture consists of component(s) of unknown toxicity.

· Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

(Contd. on page 2)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 02/02/2021 Reviewed on 02/02/2021

Trade Name: Artificial Sebum, ASTM D4265 - 14

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



· Hazard(s) not otherwise classified (HNOC): None

3 Composition/Information on Ingredients

- · Chemical characterization: Substance
- · Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous Components:		
CAS: 8001-31-8 RTECS: GG6040000	Fractionated Coconut Oil (Caprylic/Capric Triglycerides)	15-35%
CAS: 8002-74-2 RTECS: RV 0350000	Paraffin Waxes	2-12%
CAS: 57-11-4 RTECS: WI 2800000	Stearic Acid, pure • Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	2-12%

· Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

Product contains trace amounts of naturally occurring amino acids and low level salts.

4 First-Aid Measures

- · Description of first aid measures
- · General information: If symptoms persist, call a physician.
- · After inhalation:

Not anticipated under normal use.

In case of unconsciousness place patient stably in the side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

· After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

If easy to do so, remove contact lenses if worn.

If eye irritation occurs, consult a doctor.

- · After swallowing: If swallowed and symptoms occur, consult a doctor.
- · Information for doctor
- · Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5 Fire-Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 02/02/2021 Reviewed on 02/02/2021

Trade Name: Artificial Sebum, ASTM D4265 - 14

- · For safety reasons unsuitable extinguishing agents: No further relevant information.
- · Special hazards arising from the substance or mixture: No further relevant information available.
- Advice for firefighters
- · Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures: Ensure adequate ventilation.
- · Environmental precautions: No special measures required.
- · Methods and material for containment and cleaning up:

Use the appropriate tools to collect the material and dispose of it in an approved waste disposal container. Dispose of the collected material according to regulations.

· Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

· PAC-1:		
57-10-3	Palmitic acid	0.19 mg/m ³
112-80-1	Oleic acid, pure	220 mg/m ³
57-11-4	Stearic Acid, pure	14 mg/m³
111-02-4	2,6,10,15,19,23-hexamethyltetracosa-2,6,10,14,18,22-hexaene	
· PAC-2:		
57-10-3	Palmitic acid	2.1 mg/m ³
112-80-1	Oleic acid, pure	2,400 mg/m ³
57-11-4	Stearic Acid, pure	150 mg/m ³
111-02-4	2,6,10,15,19,23-hexamethyltetracosa-2,6,10,14,18,22-hexaene	90 mg/m³
· PAC-3:		
57-10-3	Palmitic acid	12 mg/m³
112-80-1	Oleic acid, pure	15,000 mg/m³
57-11-4	Stearic Acid, pure	910 mg/m³
111-02-4	2,6,10,15,19,23-hexamethyltetracosa-2,6,10,14,18,22-hexaene	540 mg/m³

7 Handling and Storage

- · Handling
- · Precautions for safe handling:

Avoid contact with skin, eyes and clothing

Use personal protection equipment as outlined in section 8.

- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and receptacles:

Store refrigerated

Shelf Life: 1 year from the date of manufacture

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 02/02/2021 Reviewed on 02/02/2021

Trade Name: Artificial Sebum, ASTM D4265 - 14

· Specific end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters:
- · Components with occupational exposure limits:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituents have no known exposure limits.

,	, a tille tille, tile remaining concataonte have ne known expective innie.		
8001	8001-31-8 Fractionated Coconut Oil (Caprylic/Capric Triglycerides)		
TWA	TWA Long-term value: 6		
8002	8002-74-2 Paraffin Waxes		
REL	Long-term value: 2 mg/m³		
TLV	Long-term value: 2 mg/m³		

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls:
- · Personal protective equipment
- General protective and hygienic measures:

Use adequate exhaust ventilation to prevent inhalation of product vapors.

Do not eat or drink while handling product.

Immediately remove all soiled and contaminated clothing.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

Respiratory protection is not required unless handling of the material produces nuisance airborne concentrations.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves: Latex or vinyl
- Penetration time of glove material:

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection:



Tightly sealed goggles

- · **Body protection:** Lab coat
- Limitation and supervision of exposure into the environment: None

(Contd. on page 5)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 02/02/2021 Reviewed on 02/02/2021

Trade Name: Artificial Sebum, ASTM D4265 - 14

9 Physical and Chemical Properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Solid
Color: White
Odor: Odorless
Odor threshold: Not determined.

pH-value: Not applicable.

· Change in condition

Melting point/Melting range: Not determined.

· Flash point: None

Flammability (solid, gaseous): Not determined.
 Ignition temperature: Not applicable
 Decomposition temperature: Not determined.

· Auto igniting: Product is not self-igniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower:
Upper:
Not determined.
Vapor pressure:
Not applicable.

Density:
Relative density:
Vapor density:
Vapor density:
Evaporation rate:
Not determined.
Not applicable.
Not applicable.

· Solubility in / Miscibility with:

Water: Soluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not applicable. **Kinematic:** Not applicable.

· Solvent content:

VOC content: 0.00 %

· Other information: No further relevant information available.

10 Stability and Reactivity

- · Reactivity: No further relevant information available.
- · Chemical stability: Stable under normal conditions.
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 6)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 02/02/2021 Reviewed on 02/02/2021

Trade Name: Artificial Sebum, ASTM D4265 - 14

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects:
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
8001-31-8	8001-31-8 Fractionated Coconut Oil (Caprylic/Capric Triglycerides)		
Oral	LD50	>5,000 mg/kg (Rat)	
8002-74-2	8002-74-2 Paraffin Waxes		
Oral	LD50	>5,000 mg/kg (Rat)	
Dermal	LD50	>2,000 mg/kg (Rabbit)	
Inhalative	LC50/96 hours	>100 mg/l (Trout)	
57-11-4 Stearic Acid, pure			
Dermal	LD50	>5,000 mg/kg (Rabbit)	

- · Primary irritant effect:
- · On the skin: Irritant to skin and mucous membranes.
- · On the eye: Irritating effect.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- · Carcinogenic categories:
- · IARC (International Agency for Research on Cancer):

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

57-88-5 Cholesterol	3
· NTP (National Toxicology Program):	
None of the ingredients are listed.	
· OSHA-Ca (Occupational Safety & Health Administration):	
None of the ingredients are listed.	

12 Ecological Information

· Toxicity:

· Aquatic toxicity:	
8002-74-2 Paraffin Waxes	
EC50 >10,000 mg/l (Daphnia)	

- · Persistence and degradability: No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.
- Additional ecological information:
- · General notes:

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

(Contd. on page 7)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 02/02/2021 Reviewed on 02/02/2021

Trade Name: Artificial Sebum, ASTM D4265 - 14

- · Results of PBT and vPvB assessment:
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.
- Other adverse effects: No further relevant information available.

13 Disposal Considerations

- · Waste treatment methods
- · Recommendation:

This product may be mixed with a combustible solvent and burned in a chemical incinerator equipped with an after burner and scruber. This product can also be sent to an EPA approved waste disposal facility. Observe all federal, state and local environmental regulations when disposing of this material.

- · Uncleaned packaging
- · Recommendation: Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport Information

· UN-Number:

· DOT, ADR/ADN, ADN, IMDG, IATA Non-Regulated Material

· UN proper shipping name:

· DOT, ADR/ADN, ADN, IMDG, IATA Non-Regulated Material

· Transport hazard class(es):

· DOT, ADR/ADN, ADN, IMDG, IATA

· Class: Non-Regulated Material

Packing group:

· DOT, ADR/ADN, IMDG, IATA Non-Regulated Material

Environmental hazards: Not applicable.
 Special precautions for user: Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code: Not applicable.

· UN "Model Regulation": Non-Regulated Material

15 Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture:

No further relevant information available.

· SARA (Superfund Amendments and Reauthorization):

· SARA (Su	perruna Amenaments and Reauthorization):	
· Section 3	55 (extremely hazardous substances):	
None of the	e ingredients are listed.	
· Section 3	13 (Specific toxic chemical listings):	
None of the	e ingredients are listed.	
· TSCA (To	xic Substances Control Act):	
8001-25-0	Virgin Olive oil	ACTIVE
8001-31-8	Fractionated Coconut Oil (Caprylic/Capric Triglycerides)	ACTIVE
57-10-3	Palmitic acid	ACTIVE
112-80-1	Oleic acid, pure	ACTIVE
8002-74-2	Paraffin Waxes	ACTIVE
57-11-4	Stearic Acid, pure	ACTIVE
57-88-5	Cholesterol	ACTIVE

(Contd. on page 8)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 02/02/2021 Reviewed on 02/02/2021

Trade Name: Artificial Sebum, ASTM D4265 - 14

60-33-3 linoleic acid, pure	ACTIVE
111-02-4 2,6,10,15,19,23-hexamethyltetracosa-2,6,10,14,18,22-hexaene	ACTIVE
Hazardous Air Pollutants	
None of the ingredients are listed.	
California Proposition 65:	
Chemicals known to cause cancer:	
None of the ingredients are listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients are listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients are listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients are listed.	
New Jersey Right-to-Know List:	
8002-74-2 Paraffin Waxes	
New Jersey Special Hazardous Substance List:	
None of the ingredients are listed.	
Pennsylvania Right-to-Know List:	
112-80-1 Oleic acid, pure	
8002-74-2 Paraffin Waxes	

· Carcinogenic categories:

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH):

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



· Signal word: Warning

· Hazard statements:

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary statements:

P264 Wash thoroughly after handling.

P280 Wear protective gloves / eye protection / face protection.

P302+P352 If on skin: Wash with plenty of water.



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 02/02/2021 Reviewed on 02/02/2021

Trade Name: Artificial Sebum, ASTM D4265 - 14

P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/attention. P332+P313 P362+P364 Take off contaminated clothing and wash it before reuse. P337+P313 If eye irritation persists: Get medical advice/attention.

· National regulations:

None of the ingredients are listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

<u> 6 Other Information</u>

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

- · Contact:
- · Date of last revision/ revision number: 02/02/2021 / 7
- · Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106